

# GLEAM LIGHT INDIA

Beginning of a new Era



An ISO 9001:2015  
Certified Company



## MIMO OMNI CYLINDRICAL ANTENNA

### Technical Specifications:

Model No-	MICYMNI012
Frequency Range -	698-960-1710-2700 MHz
VSWR -	≤1.5
Gain-dBi -	12Dbi
F/B ratio	less than 18dB
Vertical Lobe Width(°)-	55/45
Lightning Protection-	DC Ground
Operating Temperature--	40?~+85
Maximum Input Power-	50W
Polarization-	Vertical
Impedance-ohm	50
Connector-	NF/NM/SMA/Customized
Radome material-	Fiberglass
Length -	235 mm Approx
Compliances	CE Compliant
ROHS	ROHS compliant
Radome colour-	White
Mounting Method-	Pole Mount
Cable Length	5 Meter X 2 /Customized



### Product Features:-

- Multiple Frequencies
- Omni-directional radiation pattern
- Low interference
- Broad frequency range
- Durability
- Compact size



[www.gleamlightindia.in/gleamlightindia.com](http://www.gleamlightindia.in/gleamlightindia.com)

[Info@gleamlightindia.com](mailto:Info@gleamlightindia.com) 8800386366

10-A FIRST FLOOR, RAJENDRA PARK EXTN New Delhi -110041