

# 5G Flat Omni Ceiling Antenna



An ISO 9001: 2015 Certified Company



## Technical Specifications

Model No.	FLOMNI5G06
Frequency Range	698-960MHz / 1710MHz - 2170 MHz / 2300-2700MHz / 3400-4000MHz
Gain	2/6 Dbi
VSWR	2.0/1.8 max
Impedance	50 $\Omega$
Polarization	Horizontal
Inter Modulation	-150 dBc @ 2 x 33dBm IM3
Input Power max.	50 W
Radom Materia	ABS
Radom Color	White
Operation Temperature	40 to +55 °C
Environmental Class	IP65
Number of Input Ports	1
Application	Indoor
Connectors	N Type female
Pigtail Cable	Approx. 300 mm
Mounting Hardware included	Mounting Clamp
Height	18 mm
Diameter	220 mm
Width	4.3 mm
Length	4.3mm
Weight	0.3 Kg
ROHS	Compliant

## FEATURES

2G/3G/4G/5G wireless services  
Low return loss, Stable performance  
Pigtail with N Female connector  
Ceiling mounting



CALL OR  +91-8800386366

Follow Us For More Updates GLEAMLIGHTINDIA /       
[Info@gleamlightindia.com](mailto:Info@gleamlightindia.com)/[www.gleamlightindia.in](http://www.gleamlightindia.in)/[www.gleamlightindia.com](http://www.gleamlightindia.com)/[www.gleamindia.com](http://www.gleamindia.com)

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041