

5G MIMO OMNI Ceiling Antenna



An ISO 9001: 2015 Certified Company




Technical Specifications


Model No.	MIMOFOC035
Frequency Range	698-806 / 806-960 / 1710-2700 / 3300-3800MHz
Gain	3/5 Dbi
VSWR	$\leq 2.0 / \leq 1.8 / \leq 1.8 / \leq 2.0$
Polarization Type	$\pm 45^\circ$
Vertical Beamwidth	$90^\circ / 85^\circ / 45^\circ / 35^\circ$
Horizontal Beamwidth	360°
PIM	$\leq -153 \text{ dBc @ } 2 \times 43 \text{ dBm IM3}$
Max Power	50 W
Input Impedance	50Ω
Operating Temperature	$-40^\circ \text{C to } +65^\circ \text{C}$
Relative Humidity	5 to 95%
Lightning Protection	DC ground
Connector Type	N-Female/ Customized
Weight	0.5 Kg
Dimension	$\Phi 218 \times 40 \text{ mm (without connector)}$
Radome Material	Uv-Protected ABS
Radome Color	White
Mounting Type	Ceiling Installation
Cable	RG 141/RG 58 (Pure Copper)
Cable Length	Customized
ROHS	Compliant

**Horizontal
pattern**


900 MHZ






1710 MHZ



2500 MHZ



**Vertical
pattern**



CALL OR **+91-8800386366**

Follow Us For More Updates [GLEAMLIGHTINDIA /](#)
Info@gleamlightindia.com / www.gleamlightindia.in / www.gleamlightindia.com / www.gleamindia.com

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041