

BNC Female Connector For RG 179 Cable



An ISO 9001: 2015 Certified Company



Technical Specifications:

Characteristic Impedance	75 Ohm
Frequency Range	0-3 GHz
VSWR	<1.2
Dielectric Withstanding Voltage	≥2500V RMS, at sea level
Dielectric Resistance	≥5000MΩ
Contact Resistance	Center Contact ≤ 1.5 m Ω Outer Contact ≤ 1.0 m Ω
Durability	Mating Cycles ≥500
Operating Temperature Range	- 10°C – +55 °C
Durability Mating	cycle ≥500
Connector Body Style	Straight
Coaxial Termination	Crimp
For Cable	RG179 Cable
Connector Mounting	Cable Mount
RoHs	Compliant

Material and Plating:

Item	Material	Material
Body	Brass	White Bronze
Insulator	PTFE(Teflon)	-
Center conductor	Phosphor Copper	Gold(AU)



CALL OR  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

Info@gleamlightindia.com / www.gleamlightindia.in / www.gleamlightindia.com / www.gleamindia.com

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041