

CDMA CEILING OMNI ANTENNA



An ISO 9001: 2015 Certified Company



Technical Specifications:

| | |
|-------------------------|-----------------------------|
| Model No- | CDMACOA240 |
| Frequency Range (MHz) - | 824-900 MHz |
| Polarization- | Vertical |
| Gain- | 2/4 dBi |
| Horizontal Lobe width - | 360° |
| Vertical Lobe width - | 55° |
| Lightning Protection - | DC Ground |
| VSWR - | ≤1.5 |
| Maximum Input Power - | 100 W |
| Impedance - | 50ohm |
| Connector Type - | N Female/SMA/TNC/Customized |
| Operating Temp - | 40-60 |
| Radome Material - | ABS/PP |
| Radome Color - | White |
| Cable - | RG58 |
| Cable Length - | 330 mm/Customized |
| Weight - | 550 Gram |
| Packing Size - | 6.5X6.25X5.5 |



CALL OR  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     
Info@gleamlightindia.com www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041