

# Directional Coupler



An ISO 9001:2015 Certified Company



## Technical Specifications

Model No.	DIRCOU0406	DIRCOU0708	DIRCOU0910	DIRCOU1315	DIRCOU1929	
Frequency	800-2500	800-2700	698-2700 MHz			
Product Name	5/6	7/8	10	13/15	20	
Coupling	6±0.8	10±1.0	15±1.0	20±1.2	30±1.5	dB
Insertion Loss	1.75	0.8	0.45	0.4	0.35	dB
VSWR	≤1.25:1					
Power Capacity	200W					
PIM3	≤-150dBc@2×43dBm					
RF Connector	N-female or SMA-female					
Impedance	50Ω					
Relative Humidity	5%-95%					
Color	Black-plated					
Temperature	-35~+125°C					
Application	Indoor					
Weight	Light Weight					
Compliances	CE compliant					
ROHS	ROHS Compliant					

**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

[Info@gleamlightindia.com](mailto:Info@gleamlightindia.com) / [www.gleamlightindia.in](http://www.gleamlightindia.in) / [www.gleamlightindia.com](http://www.gleamlightindia.com) / [www.gleamindia.com](http://www.gleamindia.com)

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

