

GSM RUBBER DUCK ANTENNA



An ISO 9001: 2015 Certified Company



Technical Specifications:

| | |
|-------------------------|-------------------|
| Model No | GSMIDSMA09 |
| Frequency Range (MHz) | 824~894/1710~2170 |
| Polarization | Linear |
| Gain | 9 DBI |
| VSWR | ≤ 2 |
| Maximum Input Power (W) | 50 |
| Impedance(ohm) | 50 |
| Connector Type | SMA M / RP SMA M |
| Operating Temp | -40 °C to +80 °C |
| Radome Material | ABS/PP |
| Radom Color | Black |



CALL OR  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     
Info@gleamlightindia.com www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com
12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

GSM RUBBER DUCK ANTENNA



An ISO 9001: 2015 Certified Company

Gain 9 DBI

824-2170 MHZ

Rubber Protector, Waterproof and Prevent from Oxidization

High-quality interface

Quality Screw interface, makes the connection closer and signal more stable

Wide Angle

90°-180°

14.4
inch

1.42 inch



CONNECTOR TYPE



RP SMA M



SMA M



CALL OR  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     
Info@gleamlightindia.com www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041