

GLEAM LIGHT INDIA

Beginning of a new Era



An ISO 9001:2015
Certified Company



MIMO CEILING OMNI ANTENNA

Technical Specifications:

Model No.-	MIMOIDG014
Frequency Range-	698-960/1710-2700 MHz
Polarization-	Linear
Gain-	2/4 Dbi
Horizontal Lobe width-	63°
Vertical Lobe width-	55°
Lightning Protection-	DC Ground
VSWR-	≤1.5
Maximum Input Power-	100W
Impedance-	50
F/B-	18
Connector Type-	N Female/SMA/TNC/Customized
Operating Temp -	40-60 °C
Radome Material-	ABS/PP
Radome Color-	White
Brand -	Gleam Light India
Compliances -	CE Compliant
ROHS -	Compliant

Product Features:-

- Low Profile aesthetically neutral housing
- Mounts directly and easily to ceiling tile
- Wide bandwidth 700/850/900/1800/1900/UMTS/2300/2400/2500
- Two radiating elements optimized for indoor MIMO Applications
- Low cross correlation between radiating elements



 www.gleamlightindia.in/gleamlightindia.com

 Info@gleamlightindia.com / 8800386366

 12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, 110041