

# N Male For LMR 400 CRIMP Connector



An ISO 9001: 2015 Certified Company



## Technical Specifications

Characteristic Impedance	50 ohm
Frequency Range	DC-6 Ghz
VSWR	$\leq 1.15$ @DC-3GHz
Dielectric Withstanding Voltage	$\geq 1000$ V RMS,50Hz,at sea level
Dielectric Resistance	$\geq 5000$ M $\Omega$
Contact Resistance	Center Contact $\leq 1$ m $\Omega$ Outer Contact $\leq 0.25$ m $\Omega$

## Mechanical:-

Durability	Mating Cycles $\geq 500$
------------	--------------------------

## Material and Plating:-

	Material	Plating
Body	Brass	Ni
Insulator	PTFE(Teflon)	—
Center conductor	Brass	Au

## Environmental:-

Operating Temperature Range	$-40^{\circ}\text{C} \sim +85^{\circ}\text{C}$
RoHs	Compliant



**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /       
Info@gleamlightindia.com www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041