

GLEAM LIGHT INDIA

Beginning of a new Era



An ISO 9001:2015
Certified Company

 GLEAMLIGHTINDIA  GLEAMLIGHTINDIA  GLEAMLIGHTINDIA  GLEAMLIGHTINDIA

MIMO OMNI CYLINDRICAL ANTENNA

Technical Specifications:

Model No.-	MICYMNI012
Frequency Range -	698-960-1710-2700 MHz
VSWR -	≤1.5
Gain-	12Dbi
F/B ratio -	less than 18dB
Vertical Lobe Width -	55/45°
Lightning Protection -	DC Ground
Operating Temperature -	-40?~+85°C
Maximum Input Power -	50W
Polarization -	Vertical
Impedance -	50Ω
Connector-	NF/NM/SMA/Customized
Radome material -	Fiberglass
Length -	235 mm Approx.
Compliances -	CE Compliant
ROHS -	ROHS compliant
Radome color -	White
Mounting Method -	Pole Mount
Cable Length -	5 Meter X 2 /Customized



Product Features:-

- Multiple Frequencies Omni-directional radiation pattern Low interference
- Broad frequency range
- Durability
- Compact size



 www.gleamlightindia.in/gleamlightindia.com

 Info@gleamlightindia.com / 8800386366

 12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, 110041