

RG 214 Coaxial Cable



An ISO 9001:2015 Certified Company



Technical Specifications:

Performance

Cutoff Frequency	4 GHz
Characteristics Impedance	50Ω
V.S.W.R	1.2
Capacitance	101.0pF/m
Min. Bending Radius	55.2mm
Nominal Weight	0.18kg/m
DC Resistance(Inner Conductor)	1.77Ω/km
DC Resistance(Outer Conductor)	1.9Ω/km
Peak Power Rating	40KW
Temp Range	-25° to +85°C
Color	Black
Jacket Marking	GLI RG-214 Coaxial Cable/ OCT RG-214 Coaxial Cable
ROHS	Compliant

Attenuation & Power

Frequency (MHz)	Attenuation (db/100m,5-10% Increment allowance)
100MHz	6.6
400MHz	14.1
1000MHz	24.0
3000MHz	46.6

Construction

Item	Material	Diameter (inch)
• Center Conductor	Bare Copper wire	7/0.752
• Insulation	Solid PE	7.24
• Shield	Double Copper wire barding	93%+90%
• Jacket	PVC	10.8

CALL OR  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

Info@gleamlightindia.com / www.gleamlightindia.in / www.gleamlightindia.com / www.gleamindia.com

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

