

SMA MALE CONNECTORS FOR LMR 200/RG-58 RIGHT ANGLE



An ISO 9001: 2015 Certified Company



Technical Specifications:

Characteristic Impedance	50 ohm
Frequency Range	DC-6GHz
VSWR	$\leq 1.15 @ DC-6GHz$
Dielectric Withstanding Voltage	$\geq 1000V$ RMS, 50Hz, at sea level
Dielectric Resistance	$\geq 5000M\Omega$
Contact Resistance	Center Contact $\leq 3m\Omega$ Outer Contact $\leq 2.5m\Omega$
Durability	Mating Cycles ≥ 500
Operating Temperature Range	$-40^{\circ}C \sim +85^{\circ}C$
RoHs	Compliant

Material and Plating:

Item	Material	Material
Body	Brass	Au
Insulator	PTFE(Teflon)	-
Center conductor	Phosphor Copper	Au



CALL OR  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

Info@gleamlightindia.com / www.gleamlightindia.in / www.gleamlightindia.com / www.gleamindia.com

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041