

# SMA MALE PANEL MOUNT BULK HEAD CONNECTORS



An ISO 9001: 2015 Certified Company



## Technical Specifications:

Characteristic Impedance	50 ohm
Frequency Range	DC-12.4 Ghz
VSWR	≤1.15@DC-6GHz
Dielectric Withstanding Voltage	≥1000V RMS,50Hz,at sea level
Dielectric Resistance	≥5000MΩ
Contact Resistance	Center Contact ≤3mΩ Outer Contact ≤2.5mΩ
Durability	Mating Cycles ≥500
Operating Temperature Range	-40°C~+85°C
RoHs	Compliant

## Material and Plating:

Item	Material	Material
Body	Brass	Au
Insulator	PTFE(Teflon)	-
Center conductor	Phosphor Copper	Au



**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

[Info@gleamlightindia.com](mailto:Info@gleamlightindia.com) / [www.gleamlightindia.in](http://www.gleamlightindia.in) / [www.gleamlightindia.com](http://www.gleamlightindia.com) / [www.gleamindia.com](http://www.gleamindia.com)

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041