



An ISO 9001: 2015 Certified Company

# TNC Female Straight B/H Connector For RG 316



## Technical Specifications:

Characteristic Impedance	50 ohm
Frequency Range	0-3 GHz
VSWR	$\leq 1.10(0\sim 2.2G) \leq 1.15(0\sim 3G)$
Dielectric Withstanding Voltage	$\geq 2500V$ RMS, at sea level
Dielectric Resistance	$\geq 5000M\Omega$
Contact Resistance	Center Contact $\leq 1.0 m \Omega$ Outer Contact $\leq 0.25 m \Omega$
Durability	Mating Cycles $\geq 500$
Operating Temperature Range	- 40°C – +85 °C
RoHs	Compliant

## Material and Plating:

Item	Material	Material
Body	Brass	Au
Insulator	PTFE(Teflon)	-
Center conductor	Phosphor Bronze	Au



**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

[Info@gleamlightindia.com](mailto:Info@gleamlightindia.com) / [www.gleamlightindia.in](http://www.gleamlightindia.in) / [www.gleamindia.com](http://www.gleamindia.com)

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041