

# UHF Male Clamp Type For LMR 400



An ISO 9001: 2015 Certified Company



## Technical Specifications:

Characteristic Impedance	50 ohm
Frequency Range	DC-300 MHz
VSWR	$\leq 1.07$
Dielectric Withstanding Voltage	$\geq 2000V$ RMS, at sea level
Dielectric Resistance	$\geq 5000M\Omega$
Contact Resistance	Center Contact $\leq 5M \Omega$ Outer Contact $\leq 5M \Omega$
Durability	Mating Cycles $\geq 500$
Operating Temperature Range	- 40°C – +85 °C
Connector Mounting	Cable Mount
RoHs	Compliant

## Material and Plating:

Item	Material	Material
Body	Brass	Gold/nickel
Dielectric	PTFE(Teflon)	Ni
Center conductor	Brass	Au



**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     

[Info@gleamlightindia.com](mailto:Info@gleamlightindia.com) / [www.gleamlightindia.in](http://www.gleamlightindia.in) / [www.gleamindia.com](http://www.gleamindia.com)

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041