

# GSM RUBBER DUCK ANTENNA



An ISO 9001: 2015 Certified Company



## Technical Specifications:

Model No	GSMIDSMA03
Frequency Range	824~894/1710~2170MHz
Polarization	Linear
Gain	3 dBi (Zenith)
VSWR	≤2.5
Maximum Input Power	80 W
Impedance	50 Ω
Connector Type	SMA M / RP SMA M
Operating Temp	--40° to 80°C
Radome Material	ABS/PP
Radom Color	Black
ROHS	Compliant
Brand	Gleam Light India
Compliances	CE compliant



**CALL OR**  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA /**       
Info@gleamlightindia.com /www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

# GSM RUBBER DUCK ANTENNA



An ISO 9001: 2015 Certified Company

## Gain 3 DBI

824-2170 MHZ

Rubber Protector, Waterproof and Prevent from Oxidization

### High-quality interface

Quality Screw interface, makes the connection closer and signal more stable

### Wide Angle

90°-180°

4.8  
inch



## CONNECTOR TYPE



SMA M



RP SMA M



CALL OR  +91-8800386366

Follow Us For More Updates **GLEAMLIGHTINDIA** /       
Info@gleamlightindia.com /www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041