

GSM RUBBER DUCK ANTENNA




An ISO 9001: 2015 Certified Company




Technical Specifications:

Model No	GSMIDSMA09
Frequency Range (MHz)	824~894/1710~217
Polarization	0 Linear
Gain	9 DBI
VSWR	≤2
Maximum Input Power	50W
Impedance	50 ohm
Connector Type	SMA M / RP SMA M
Operating Temp	-40 °C to +80 °C
Radome Material	ABS/PP
Radom Color	Black
ROHS	compliant
Brand	Gleam Light India
Compliances	CE compliant



CALL OR  **+91-8800386366**

Follow Us For More Updates **GLEAMLIGHTINDIA** /     
Info@gleamlightindia.com/ www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com
12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041

GSM RUBBER DUCK ANTENNA



An ISO 9001: 2015 Certified Company



Gain 9 DBI

824-2170 MHZ

Rubber Protector, Waterproof and Prevent from Oxidization



High-quality interface

Quality Screw interface, makes the connection closer and signal more stable



Wide Angle

90°-180°

CONNECTOR TYPE



RP SMA M



SMA M



CALL OR  +91-8800386366

Follow Us For More Updates [GLEAMLIGHTINDIA /](#)     
Info@gleamlightindia.com /www.gleamlightindia.in/gleamlightindia.com/www.gleamindia.com

12B Block -A, Behind Kanishka Garden, Amar Colony Main Rohtak Road Nangloi, New Delhi, Delhi 110041